

ELECTRICAL LEGEND	
	SINGLE POLE SWITCH
	DIMMER SWITCH
	DUPLEX OUTLET
	DUPLEX OUTLET @ 2" A.S. *
	GFI DUPLEX OUTLET
	WATERPROOF DUPLEX OUTLET
	1/2 SWITCHED OUTLET
	FLOOR OUTLET
	CEILING MOUNTED FIXTURE OR PENDANT
	WALL MOUNTED FIXTURE
	RECESSED LED CEILING FIXTURE (CANS)
	RECESSED LED CEILING FIXTURE, DIRECTIONAL
	CEILING MOUNTED LONG LED FIXTURE
	WALL MOUNTED LONG LED FIXTURE
	OVER CABINET, LED
	UNDER CABINET, LED
	TRACK LIGHTING
	FLOOD LIGHTS
	TELEPHONE + CAT 5 DATA OUTLET
	DOOR CHIMES
	CABLE TELEVISION OUTLET
	SMOKE DETECTOR
	THERMOSTAT
	STEREO SPEAKER OUTLET
	STEREO JUNCTION
	JUNCTION BOX
	CAN FAN ON TIMER
	CEILING MOUNTED EXHAUST FAN ON TIMER
	CEILING FAN
	CEILING FAN WITH LIGHTS
	ELECTRICAL PANEL
	ELECTRICAL METER
	SECURITY PANEL
	TELEPHONE BOX LOCATION
	FUTURE WIRING
	MOTION SENSOR

WINDOW SCHEDULE	
REMARKS	
1. WINDOWS SHALL BE LOW-E WITH NFRC RATED U VALUE OF .32 OR LESS 2. WINDOWS SHALL HAVE A 10 YEAR WARRANTY ON ALL INSULATED GLAZING 3. PROVIDE JAMB EXTENSIONS TO MATCH WALL THICKNESS 4. DIMENSIONS ARE APPROXIMATE ROUGH OPENING SIZES, VERIFY ACTUAL ROUGH OPENING SIZE WITH MFR BEFORE FRAMING 5. GLAZING TO BE CLEAR, INSULATED, LOW-E 6. EGRESS WINDOWS PER CODE 7. GLAZING TO BE TEMPERED PER CODE 8. PROVIDE SCREENS ON ALL OPERABLE WINDOWS 9. PROVIDE FALL PROTECTION HARDWARE PER CODE	

DOOR SCHEDULE

MARK	DOOR	FRAME	MISC.	REMARKS							
	TYPE	SIZE	MATERIAL	FINISH	MATERIAL	FINISH	DETAIL	FIRE-RESISTANCE	HARDWARE	NOTES	
101	B	3'0x7'0"	WD	STAIN	WD	P	-	-	-	-	EXTERIOR DOOR
102	A	2'8x6'8"	WD	P	WD	P	-	-	-	-	
103	A	2'4x6'8"	WD	P	WD	P	-	-	-	-	
104	A	2'0x6'8"	WD	P	WD	P	-	-	-	-	
105	A	2'6x6'8"	WD	P	WD	P	-	-	-	-	
106	A	2'8x6'8"	WD	P	WD	P	-	-	-	-	
107	A	2'8x6'8"	WD	P	WD	P	-	-	-	-	
108	A	2'8x6'8"	WD	P	WD	P	-	-	-	-	
109	A	2'8x6'8"	WD	P	WD	P	-	-	-	-	TOP OF DOOR SLOPES TO MATCH CEILING
110	A	2'8x6'8"	WD	P	WD	P	-	-	-	-	TOP OF DOOR SLOPES TO MATCH CEILING

DOOR TYPES

PANEL STYLE TBD

A

B